

# Kodak

## Magnus 800 Platesetter



### High-performance plate making with top image quality

Kodak Magnus 800 Platesetters provide exceptional productivity and efficiency to meet the needs of both small and large commercial printers. They offer speeds up to 60 plates per hour, a modular design for easy scalability, and various plate options including environmentally friendly non process plates. The Kodak Magnus 800 Quantum Platesetter, combined with 10-micron Kodak Staccato Screening and Kodak Digital Plates, delivers photorealistic results that you have to see to believe.

### Advanced automation for flexibility and productivity

Multiple automation options—from the semi-automatic base unit, to single- or multi-cassette units, to the new Automatic Pallet Loader—support your unique business needs.

The Automatic Pallet Loader (APL) for the Magnus 800 Platesetter enables faster plate loading, reduced labor costs, and longer unattended operation. Simply load a pallet of up to 600 plates into the APL bay, and the machine does the rest, removing slip sheets and loading each plate automatically into the platesetter.

### Greater throughput, with upgrade potential

The Magnus 800Z Quantum Platesetter is the fastest 8-page CTP device in the market, with a throughput of 60 plates per

hour. In addition, you can choose from 15, 22, 30, and 40 plate per hour systems that meet your requirements today, and easily upgrade as your business grows.

### Maximum stability

Standard on all Magnus 800 Platesetters, Kodak SQUAREspot Imaging Technology automatically compensates for temperature-related plate expansion and contraction for precise, consistent imaging from plate to plate and machine to machine. SQUAREspot Technology also enables Kodak Staccato Screening for moiré-free image fidelity with extraordinary tone and color consistency throughout the press run. Additionally, the dynamic autofocus mechanism provides robustness to process variation on the plate and prevents hot spots.

### Seamless integration with Kodak Solutions

The Magnus 800 Platesetter is tightly integrated with Kodak Workflow Solutions, Kodak Processing Equipment and Kodak Plates, enabling a complete automated prepress solution. Third party workflow systems are also easily integrated.

### Reduce costs and environmental impact

The Magnus 800 Platesetter family supports Kodak Thermal Direct Non Process Plates and other processless plates, so you can completely eliminate your processor and chemistry.

# Kodak Magnus 800/ Magnus 800 Quantum Platesetters

	Magnus 800 Platesetter	Magnus 800 Quantum Platesetter
<b>General specifications</b>		
Technology	830 nm thermal imaging platesetter, fully or semiautomatic, external drum	
Load/unload systems	<ul style="list-style-type: none"> <li>• ContinuousLoad: Semiautomated; as one plate is imaged, another is placed on standby for automatic loading as soon as the drum unloads.</li> <li>• Single-cassette unit (SCU) option: Fully automated; holds up to 100 plates of the same size and thickness with slip sheets. Can be configured in left or right orientation.</li> <li>• Multi-cassette unit (MCU) option: Fully automated; holds up to 500 plates in 5 cassettes, each containing up to 100 plates of the same size and thickness with slip sheets. The required cassette is automatically selected according to the job definition. Empty cassettes can be reloaded while the platesetter is running.</li> <li>• Automatic Pallet Loader (APL): Holds one pallet of up to 600 plates of the same size and thickness with slip sheets. Optional cassette tray for up to 100 plates. Option to bypass the automatic plate loader by inserting plate directly into the platesetter from the loading conveyor. (Consult your <b>Kodak</b> Plates representative for a current list of plates qualified for the APL.)</li> </ul>	
Inline punch	<ul style="list-style-type: none"> <li>• Up to 10 customized punch heads. Select from a list of punches qualified for <b>Magnus 800</b> Platesetter</li> <li>• Optional automatic punching is operated according to press profile selected from the <b>Kodak</b> Workflow</li> <li>• Punch is available on the front edge of the plate only.</li> </ul>	
<b>Performance specifications</b>		
Throughput at 2400 dpi <sup>1,2</sup>	S speed: 15 plates per hour F speed: 22 plates per hour V speed: 30 plates per hour X speed: 40 plates per hour Z speed: 60 plates per hour (For more information, please refer to the <b>Kodak Magnus 800Z Quantum</b> Platesetter sell sheet)	
Repeatability	± 5 microns (over 2 consecutive exposures on the same plate)	
Accuracy	± 20 microns (between 2 plates imaged on the same platesetter, at largest plate size)	
Registration	± 25 microns between image and punches, when customer punches are used (at largest plate size)	
Workflow connectivity	<b>Kodak Prinergy</b> Workflow and <b>Kodak Prinergy Evo</b> WorkflowConnection to third-party workflow systems (via 1-bit TIFF workflow)	
<b>Imaging specifications</b>		
Resolution	2400/1200 or 2540/1270 dpi	
Screening	250 lpi max linescreen 25-micron <b>Kodak Staccato</b> Screening	450 lpi max linescreen 20-micron <b>Kodak Staccato</b> Screening Optional: 10-micron <b>Kodak Staccato</b> Screening
Max. plate size: around x along drum	950 x 1162 mm (37.4 x 45.7 in.)	
Max. image area size: around x along drum	938 x 1162 mm (36.9 x 45.7 in.)	
Min. plate size: around x along drum	330 x 305 mm (13 x 12 in.)	
Min. image area size: around x along drum	318 x 305 mm (12.5 x 12 in.)	
<b>Physical characteristics</b>		
Size (H x W x D)	110 x 249.5 x 150.4 cm ( 43.3 x 98.2 x 59.2 in.)	
Weight	1040 kg (2293 lb.)	

## To learn more about solutions from Kodak:

Visit [graphics.kodak.com](http://graphics.kodak.com)

Produced using **Kodak** Technology.

Eastman Kodak Company  
343 State Street  
Rochester, NY 14650 USA

©Kodak, 2010. Kodak, Magnus, Quantum, Thermal Direct, Prinergy, Prinergy Evo, Staccato and SQUAREspot are trademarks of Kodak.

Subject to technical change without notice.

W.PS.301.0410.en.03

<sup>1</sup> Imaging time is dependent on media sensitivity and screening type. All values are for media sensitivity of 120mj/cm<sup>2</sup>, screening of 175 lpi and plate width of 1030 mm (40.55 in.)

<sup>2</sup> Tested with **Kodak** Workflow.

The platesetter is a Class 1 Laser Product and fully complies with EN60825-1 and US Federal Regulations 21 CFR 1040.10 - CDRH.



It's time for you **AND** Kodak